

FR1601 THRU FR1607

GLASS PASSIVATED FAST RECOVERY RECTIFIER

REVERSE VOLTAGE: 50 to 1000 VOLTS

FORWARD CURRENT: 16.0 AMPERE

<http://www.njzrg.com>

FEATURES

- Low forward voltage drop
- High current capability
- High capability
- High surge current capability

MECHANICAL DATA

Case: Molded plastic, TO-220A


Epoxy: UL 94V-O rate flame retardant

Terminals: Leads solderable per MIL-STD-202 method 208 guaranteed

Polarity: As marked

Mounting position: Any

Weight: 0.08ounce, 2.24gram



Maximum Ratings and Electrical Characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

	Symbols	FR1601	FR1602	FR1603	FR1604	FR1605	FR1606	FR1607	Units
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS Voltage	V _{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage	V _{DC}	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Current See Fig. 2	I _(AV)	16.0							Amp
Peak Forward Surge Current, 8.3ms single half-sine-wave superimposed on rated load (JEDEC method)	I _{FSM}	250							Amp
Maximum Forward Voltage at 16.0A DC and 25	V _F	1.3							Volts
Maximum Reverse Current at T _C =25 at Rated DC Blocking Voltage T _C =125	I _R	5.0 100							uAmp
Typical Thermal Resistance (Note 1)	R _{θJC}	2.5							/W
Maximum Reverse Recovery Time (Note 2)	T _{RR}	150				250	500		nS
Operating and Storage Temperature Range	T _J , T _{stg}	-55 to +150							

NOTES:

1- Thermal Resistance from Junction to Case Mounted on Heatsink.

2- Reverse Recovery Test Conditions : $I_F=5A$, $I_R=1A$, $I_{RR}=25A$.

FR1601 THRU FR1607

GLASS PASSIVATED FAST RECOVERY RECTIFIER

RATINGS AND CHARACTERISTIC CURVES

<http://www.njzrg.com>

FIG.1- REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM




FIG.2- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG.3- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.4- TYPICAL JUNCTION CAPACITANCE




FIG.5- TYPICAL REVERSE CHARACTERISTICS




FIG.6- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS

